

In line with Regulation (EC) No. 1907/2006 & GHS Page 1 of 4 revised: March 1st, 2023 GM--SDS-001

0. General information

According to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS), GHS applies to pure substances and their dilute solutions and to mixtures. "Articles" as defined in the Hazard Communication Standard (29 CFD 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system.

Also the European Regulation (ER) on Chemicals No. 1907/2006 (REACH) enforced on June 1st, 2007 does only require Material Safety Data Sheet (MSDS) for hazardous substances or preparations – not for articles.

All AIREX® products meet the definition of "Article" under the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS), the European Union (EU) Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) Standard, United States (US) Occupational Health and Safety Administration (OSHA) Hazard Communication Standard, Canadian Workplace Hazardous Materials Information System (WHMIS) Regulation and Australian Work Health and Safety (WHS) Regulation.

Therefore, under normal usage of the AIREX® products, no Material Safety Data Sheet (MSDS) is legally required.

To support our customers with additional data on safe handling and use instructions for our manufactured articles this Safe Use Instruction Sheet was created.

1. Identification of substance / preparation and of the company

AIREX® C70/C71 Rigid foam

(C70.40, C70.48, C70.55, C70.75, C70.90, C70.130, C70.200, C70.250, C71.55, C71.75, C71.90, C71.130)

Use of substance / preparation: Core material in sandwich constructions

Company identification: Airex AG

5643 Sins, Switzerland Tel +41 41 789 66 00

2. Hazards identification

AIREX® C70/C71 does not constitute any risk to public health and environment if it is used as intended.

Possible health issues:

- Harmful to health due to inhaling vapour and dust that may be produced by sawing, grinding and thermoforming.
- Harmful to health due to ingesting dust that may be produced by grinding and sawing.

The foam is highly resistive: it could be loaded electrically in particular after machining.

3. Composition / Information on ingredients

Rigid polymeric foam on the basis of Polyvinylchloride modified by an interpenetrating polymer network with aromatic amides.

Blowing agent: Carbon dioxide (CO₂ / produced by the reaction of water with isocyanate components), N₂.

Further ingredients: Residues of chemical blowing agent (including Diazene-1,2-dicarboxamide (C,C'-

azodi (formamide)) (ADCA, CAS-Nr. 123-77-3) (< 0.5% w/w).

Organic colour pigments. Stabilisers.

4. First aid measures

Inhalation of processing fumes: Move victim to fresh air; obtain medical attention if irritation persists.

Inhalation of gases in case of fire: Move victim to fresh air and obtain medical attention.

Skin contact: Wash with water.

Eye contact: Flush with water if irritation develops.

Ingestion: No special measures required. Seek medical attention if symptoms develop.

www.3ACcorematerials.com

Europe | Middle East | India | Africa Airex AG

5643 Sins, Switzerland T +41 41 789 66 00 corematerials@3AComposites.com North America | South America Baltek Inc. High Point, NC 27261, USA T +1 336 398 1900

T +1 336 398 1900

corematerials.americas@3AComposites.com

Asia | Australia | New Zealand 3A Composites (China) Ltd. 201201 Shanghai, China T +86 21 585 86 006

corematerials.asia@3AComposites.com



In line with Regulation (EC) No. 1907/2006 & GHS Page 2 of 4 revised: March 1st, 2023

GM--SUIS-001

5. Fire-fighting measures

Suitable extinguishing media: Foam, water spray, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used: Direct water jet.

Hazardous combustion products: Hydrogen chloride (HCI) and hydrogen cyanide (HCN), CO, CO₂.

Use respiratory protection independent of recirculated air.

6. Accidental release measures

No special measures required.

7. Handling and storage

Handling: It must be ensured that there is good ventilation and suction on the processing machines

and where dust development may occur.

Storage: Stow indoor. Stow away from immediate and dangerous sources of ignition.

Possibility of electrostatic charges when stored in very dry areas.

8. Exposure control / personal protection

General protection measures:

Sufficient air circulation is required during processing. The exhaust air must not be recirculated. If the workstation cannot be sufficiently ventilated, it is imperative that respiratory protection (A2P3 filter) is worn.

Workstation threshold values:

Dust	Source	Value type	Value (mg/m³)	Remarks
	SUVA	MAC values	10	Inhalable particles

Gasses / Vapours	Source	Value type	Value (mg/m³)	Remarks
Tetramethylsuccinonitrile	SUVA	MAC values	3	
Methacrylnitrile	SUVA	MAC values	3	

Personal protection equipment

Respiratory protection: Effective breathing mask

Hand protection: Gloves
Eye protection: Goggles

9. Physical and chemical properties

Physical state / form: Polymer foam sheet with visible cell structure.

Colour: Various, depending on density.

Glass transition temperature: 65 to 80 °C ISO 537

Decomposition temperature: > 220 °C

Flash ignition temperature: >380 °C ASTM D 1929

Density: 30 - 300 kg/m³ ISO 845

Solubility: Insoluble in: Water, sea water, acids, alkalis, aliphatic hydrocarbons

Soluble in: Aromatic hydrocarbons, Ketones, chlorinated hydrocarbons



In line with Regulation (EC) No. 1907/2006 & GHS Page 3 of 4 revised: March 1st, 2023

GM--SUIS-001

10. Stability and reactivity

General information: Stable under normal conditions

Conditions to avoid: High temperatures (> 180 °C)

Materials to avoid: Not applicable.

Flammability class S: S4 (DIN 5510-2 ed 2009)

Dangerous decomposition

Tetramethylsuccinonitrile (TMSN) Methacrylnitrile

products:

Isobutyronitrile

Hydrogen chloride (HCI)

Hydrogen cyanide (HCN) in small amounts

Carbon monoxide (CO) Carbon dioxide (CO₂)

11. Toxicological information

Toxicological tests: No data available.

Experience with man:

Skin contact: Grinding dust may cause irritation to people with sensitive skin.

Eye contact: Dust may cause irritation.

Inhalation: Dust may cause irritation of respiration tract. Dizziness, nausea and headaches may

occur if processing (sawing, grinding or tempering) is performed without sufficient ventilation and respiratory protection over several hours in small, poorly ventilated areas.

Ingestion: No symptoms known.

12. Ecological information

Ecotoxicity: The total amount of all heavy metals is <100 mg/kg [ppm].

Mobility: Not soluble in water, therefore effects on groundwater are unlikely.

Persistence and degradability: Biologically not degradable.

13. Disposal considerations

Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.

14. Transport information

Railroad RID No restriction.
Road ADR No restriction.
Sea IMDG Code No restriction.
Air ICAO-TI/IATA-DGR No restriction.
UN-Classification Not required.

15. Regulatory information

AIREX® C70/C71 rigid plastic foam does not require marking under the following directives or is not concerned by the following regulations:

- Europe: Directive 67/548/EWG, ("DSD"), Directive 1999/45/EC, ("DPD"), Regulation (EC) No 1272/2008 ("CLP").
- US: OSHA .29 CFR 1910.1200 and .49 CFR 171.8 (EPA 40 CFR 117) spill, leak and disposal regulations of the US Department of Transportation.
- Canada: WHMIS and TDG.



In line with Regulation (EC) No. 1907/2006 & GHS Page 4 of 4 revised: March 1st, 2023

GM--SUIS-001

16. Other information

This Safe Use Instruction Sheet (SUIS) replaces the issue released on August 8th, 2022.

The information given in this document is accurate to the best of our knowledge, but without any guarantee. It is given in good faith based on the current state of knowledge and experience. It is issued in respect of safety requirements and does not purpose to provide information on the quality of the material.